

Pierlux Eco IP65

Specification

- NSW IPART APPROVED.
- Stylish recessed IP65 downlight offering LED 69Lm/W, 4000K format
- The system is c/w flex & plug, for a quick installation by way of plug & play
- The downlight comes in a fixed format, and a matt white trim
- The integral acrylic lens has been designed to provide a low glare appearance and performance
- The downlight has a cut out of 90mm the overall dimensions are 115mm x 50mm
- Lamp power consumption 12 watts, (total system 14 watts)
- System is supplied with dimmable remote 650mA
- constant current driver

Product Codes

Code	Version	Dim (mm)	Cutout (mm)
ECOLED/65/1	Pierlux Eco IP 65 12W, CCT 3000K, Lumens 828lm, IP65, 30,000hrs	Ø115x50	Ø95-105
ECOLED/65/5	Pierlux Eco IP 65 12W, CCT 4000K, Lumens 828lm, IP65, 30,000hrs	Ø115x50	Ø95-105





Quick Specification

Stylish flush satin frosted lens offering a comfort controlled IP65 LED downlight. Pierlite ECO IP65 LED, frosted acrylic lens, 14W, 4000K, or 3000K, 650mA remote constant current driver c/w flex & plug, CRI >80 fixed format

Design Application

Ideal for any residential spaces such as kitchens, bathrooms, laundries and bedrooms as well as the kids play room.

Performance



Max Dim (mm)
600 or 1200

PDF Prepared: 09.09.2016 17:09pm, Last page update: Sep 2016



PIERLITE
professional lighting solutions