



Slim Downlight

Features & Benefits

- High transparency diffuser with higher lumen & better lighting effect.
- Built-in Aluminium profile for good heat dissipation.
- Thermal conductive plastic housing ensures safety.
- Elegant Design, Easy to Fix.
- Dimmable version available as an option.
- Working temperature: -20°C ~ 40°C.
- Rated life 30000 hours

Applications

- General Lighting
- Office
- Retail
- Healthcare
- Education
- Industries

Slim Downlight



Coarts LED Slim Downlight transforms ambient lighting into an exquisite balance of refined appearance and superior efficiency.

Specifications

CODE	WATTS	Voltage	PF	CRI	CCT	Lumens	Beam	IP Rating	DIM (mm)	Cutout (mm)
CLS-RMDL-6W	6 W	220-240V	>0.5	Ra>70	3000K	231 lm	120°	IP20	Ø120 X 20	Ø110
					4000K	263 lm				
					6500K	295 lm				
CLS-RMDL-12W	12 W	220-240V	>0.5	Ra>70	3000K	616 lm	120°	IP20	Ø170 X 20	Ø160
					4000K	702 lm				
					6500K	787 lm				
CLS-RMDL-18W	18 W	220-240V	>0.5	Ra>70	3000K	1000 lm	120°	IP20	Ø225 X 20	Ø215
					4000K	1139 lm				
					6500K	1278 lm				

