

Stella Flood Light

Features & Benefits

- Available in 50W, 100W and 150W
- LED efficacy > 80lm/W
- Input voltage 220-240VAC, 50/60Hz
- Power factor ≥ 0.9
- Diecast aluminium body powder coated black
- Galvanised trunnion arm powder coated black
- Ingress protection rating: IP65
- 30,000hrs rated average design life @ L70*

Stella Flood Light



Applications

Ideal for illumination over a barbeque area, driveways, illumination of trees, ensuring security in car parks, and storage yards, as well as safe illumination of entrances, pathways and building surrounds.

The Stella Flood light is an energy efficient and high performing external luminaire with a performance output of over 80lm/w and a symmetrical light distribution. Along with its compact lightweight design and rotatable trunnion arm, it offers flexible mounting options and easy installation. Suitable for low cost, high output general floodlighting applications.

Specifications

CODE	WATTS	Voltage	PF	CRI	CCT	Lumens	Beam	IP Rating	DIM (mm)	Life Time
CLS-STLFLD-50W	50 W	220-240V	>0.9	Ra>70	6000K	4400 lm	110°	IP65	185x134x21	30000 hrs
CLS-STLFLD-100W	100 W				6000K	8360 lm			240x175x30	
CLS-STLFLD-150W	150 W				6000K	12100			290x211x32	

