



Main

Range	Actassi
Product or component type	Multimode fibre optic patchcord
Colour	Sheath: orange SC duplex housing: black
Type of packing	Plastic bag

Complementary

Maximum insertion loss	0.2 dB SC
Minimum return loss	30 dB SC
Pulling force	66 N
Crush resistance	100 N/m
Fibre performance	OM2 50/125 µm
Condition of use	Patching
Exchange mode	Duplex
Mode of transmission	Multi mode
Number of optic fibre	2
Cable outer diameter	1.6 mm 2 +/- 0.2 mm
Cable length	3 m
Targeted region	Asia Pacific.

Environment

Ambient air temperature for operation	-20...60 °C
Ambient air temperature for installation	-20...60 °C
Ambient air temperature for storage	-20...60 °C
Standards	IEC 60754-1 IEC 60754-2 IEC 61034 Fibre performance: TIA/EIA-568-C.3 Fibre performance: ISO/IEC 11801:2011 Ed.2.2 OM2 SC connector: TIA/EIA-604-3 SC connector: IEC 61754-4 Ed.2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.9 cm
Package 1 Width	19.0 cm
Package 1 Length	19.0 cm
Package 1 Weight	42.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	15
Package 2 Height	14.0 cm
Package 2 Width	19.0 cm

Package 2 Length	19.0 cm
Package 2 Weight	770.0 g
Unit Type of Package 3	S04
Number of Units in Package 3	180
Package 3 Height	30.0 cm
Package 3 Width	40.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	10.24 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	No need of specific recycling operations