

ROUND SURFACE DOWNLIGHT



Coarts Round Surface Downlight offers a clean, classic and eye-appealing curvature design that transforms ambient lighting into an exquisite balance of refined appearance and superior efficiency. It is a perfect choice for retrofitting or updating existing surface mount fixtures.

Features

- Its clean and classic design makes it easy to fix and maintain for a wide range of application.
- Its surface mounted frame works as an individual fitting of surface downlight.
- Ideal for surfaces where false ceiling is not available.
- Provides good heat dissipation with built-in Aluminium profile and thermal conductive plastic housing that ensures safety.
- Working temperature: -20°C ~ 40°C.
- Available in 3000K, 4000K, 6500K color temperature options.
- Rated life 50,000hours.

Applications

- General Lighting of offices
- Retail outlets
- Healthcare facilities
- Education institutes
- Industries

Specifications

PRODUCT CODE	WATTS (W)	INPUT VOLTAGE	POWER FACTOR	COLOR TEMPERATURE	LUMENS (lm) 3000K / 4000K / 6500K	DIMENSIONS (mm)
CLS-SMDL-6W	6	85-265 VAC	>0.5	3000K / 4000K / 6500K	300 / 315 / 330	Ø110 X 28
CLS-SMDL-12W	12				840 / 880 / 925	Ø160 X 28
CLS-SMDL-18W	18				1260 / 1320 / 1390	Ø210 X 28
CLS-SMDL-24W	24				1680 / 1760 / 1850	Ø285 X 28

