

Product data sheet

HDPZ50R16

Characteristics

Distribution box, HDPZ50, metal box with plastic cover, 16 ways, flush mounted



Main

Range of product	HDPZ50
Device application	Low voltage electrical distribution
Product or component type	Empty consumer unit
Enclosure type	Insulated enclosure
Number of 18 mm modules per row	16.0
Provided equipment	Earth/neutral terminal block
Type of front cover	Transparent

Complementary

Enclosure mounting	Flush
Number of horizontal rows	1.0
Number of ways	16 ways
Enclosure material	Box: metal Cover: plastic
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Type of rail	DIN
Cable entry	Knock-out
Downside connection	Rear
Comb busbar and distribution block compatibility	YES
Product compatibility	Switch MCB RCCB RCBO
Height	343 mm
Width	200 mm
Depth	90 mm

Environment

Standards	IEC 60670
IP degree of protection	IP30
Ambient air temperature for operation	-5...60 °C

Product data sheet

HDPZ50R24

Characteristics

Distribution box, HDPZ50, metal box with plastic cover, 24 ways, flush mounted



Main

Range of product	HDPZ50
Device application	Low voltage electrical distribution
Product or component type	Empty consumer unit
Enclosure type	Insulated enclosure
Number of 18 mm modules per row	24.0
Provided equipment	Earth/neutral terminal block
Type of front cover	Transparent

Complementary

Enclosure mounting	Flush
Number of horizontal rows	2.0
Number of ways	24 ways
Enclosure material	Box: metal Cover: plastic
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Type of rail	DIN
Cable entry	Knock-out
Downside connection	Rear
Comb busbar and distribution block compatibility	YES
Product compatibility	Switch MCB RCCB RCBO
Height	282 mm
Width	364 mm
Depth	90 mm

Environment

Standards	IEC 60670
IP degree of protection	IP30
Ambient air temperature for operation	-5...60 °C