

Product data sheet

HRT1600100

Characteristics

Blade fuse, HRT16, fuse size 00, 100 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	100 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT1600125

Characteristics

Blade fuse, HRT16, fuse size 00, 125 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	125 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT1600160

Characteristics

Blade fuse, HRT16, fuse size 00, 160 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	160 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT161250

Characteristics

Blade fuse, HRT16, fuse size 1, 250 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	1

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	250 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT162315

Characteristics

Blade fuse, HRT16, fuse size 2, 315 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	2

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	315 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT162400

Characteristics

Blade fuse, HRT16, fuse size 2, 400 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	2

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	400 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT163500

Characteristics

Blade fuse, HRT16, fuse size 3, 500 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	3

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	500 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT163630

Characteristics

Blade fuse, HRT16, fuse size 3, 630 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	3

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	630 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT160063

Characteristics

Blade fuse, HRT16, fuse size 00, 63 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	63 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT160032

Characteristics

Blade fuse, HRT16, fuse size 00, 32 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	32 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT160025

Characteristics

Blade fuse, HRT16, fuse size 00, 25 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	25 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT160016

Characteristics

Blade fuse, HRT16, fuse size 00, 16 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	16 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	

Product data sheet

HRT160010

Characteristics

Blade fuse, HRT16, fuse size 00, 10 A



Main

Range of product	HRT16
Product or component type	Fuse
Fuse type	Blade type
Device application	Protection
Fuse curve	GG
Fuse size	00

Complementary

[Ue] rated operational voltage	500/690 V AC
[In] rated current	10 A

Environment

Standards	EN 60269
Product certifications	CE
Ambient air temperature for operation	-5...40 °C
Operating altitude	