


Product datasheet

Specifications



Switched Socket, ESM series, 13A, 250V, 1 gang

ESM25

Main

Range	S-Classic
Product or component type	Socket-outlet with switch
Device application	Power supply
Outlet poles configuration	2P + E
Rated current	13 A at 250 V AC 50/60 Hz

Complementary

Number of gangs	2 gangs
Device mounting	Flush Surface

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.3 cm
Package 1 Width	9.3 cm
Package 1 Length	25.8 cm
Package 1 Weight	150 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	14.3 cm
Package 2 Width	25.8 cm
Package 2 Length	5 cm
Package 2 Weight	3.6 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	27.5 cm
Package 3 Width	29.3 cm
Package 3 Length	49.5 cm
Package 3 Weight	18 kg

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	C6f2fabe-d5ba-4588-bd03-c90f7def1381
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration

Use Again

 Repack and remanufacture	
Take-back	No