

# Product datasheet

Specifications



## ESM - 10AX 250V 1 gang 2 way switch Module

ESM31\_1\_2AR\_G11

### Main

Range	S-Classic
Product or component type	Switch
Switch application	Lighting
Quantity per set	Set of 1

### Complementary

Control type	Rocker
Actuator	Rocker
Switch function	1-way
Number of gangs	1 gang
Device mounting	Flush Surface
Rated current	10 AX at 250 V AC
Number of terminals	2
Material	Dolly: PC (polycarbonate), white
Height	84 mm
Width	84 mm
Depth	45 mm

### Environment

Ambient air temperature for operation	-5...40 °C
relative humidity	0...95 %
Standards	MS IEC 60669-1 IEC 60669-1 BS EN 60669-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.4 cm
Package 1 Width	8.2 cm
Package 1 Length	25.5 cm
Package 1 Weight	215.0 g

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	3
---	---

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Under investigation
-------------------	---------------------

### Use Again

#### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
---------------------	--

Take-back	No
-----------	----