

# Lisse White moulded - socket-outlet - 15 A - 1 gang - matt white set of 1

GGBL3090S

## Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Socket-outlet
Device presentation	Complete product
Outlet standard description	Round pin
Switch function	Switch
Colour tint	Matt white
Quantity per set	Set of 1

# Complementary

Outlet poles configuration	1P
Outlet standard deviation	British
Number of gangs	1 gang
Device mounting	Wall mounted
Rated current	15 A
Fixing mode	By screws M3.5 x 25 mm
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of packing	Bag
type of installation	Indoor
Height	87 mm
Width	87 mm
Depth	35.86 mm
Product weight	0.093 kg

## **Environment**

Standards	BS 546
IP degree of protection	IP20

# **Packing Units**

Unit Type of Package 1	PCE
Noveles and Delike in Design and 4	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Package 1 Height	3.400 cm
Package 1 Width	8.700 cm
Package 1 Length	8.700 cm
Package 1 Weight	102.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.500 cm
Package 2 Width	16.500 cm
Package 2 Length	18.000 cm
Package 2 Weight	1.090 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Height	35.000 cm
Package 3 Width	38.000 cm
Package 3 Length	50.000 cm
Package 3 Weight	22.600 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration

#### **Use Again**

○ Repack and remanufacture		
Take-back	No	