

ZENcelo - 2 Gang Telephone + Data Outlet Category 6 on Shuttered Wallplate

E8432TDRJS_6_SA

Discontinued on: Jun 30, 2023 AD

(!) Discontinued

Main

Range	ZENcelo
Product or component type	Telephone + data socket
Device application	Communication
Cover frame colour tint	Silver satin
Socket additional information	Shuttered

Complementary

Rated current	1.5 A		
Communication network category	Data: 6		
	Voice: 3		
Insulation resistance	>= 200 mOhm		
Contact resistance	1 μOhm		
Number of gangs	2 gangs		
Connector type	RJ11		
	RJ45		
Material	Polycarbonate housing		
Contacts material	Contact: phosphor bronze with gold plating		
	IDC contact: phosphor bronze with nickel plating		
AWG gauge	AWG 26AWG 22 (4 twisted pair cables)		
Minimum return loss	23 dB		
Device mounting	Flush		
	Surface		
Fixing mode	By screws M4 x 25 mm		
fixing center	60.3 mm		
Width	87 mm		
Height	87 mm		
Depth	39 mm		
Embedding depth	30.6 mm		

Environment

Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	035 °C

relative humidity	095 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	129.41 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	1.235 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	12852.8 g



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

0	Environmental	factorist
4	Environmental	TOOLDITIL

Environmental Disclosure

Product Environmental Profile

Use Better

EU RoHS Directive

Compliant

China RoHS Regulation

China RoHS declaration

Use Again

○ Repack and remanufacture

Circularity Profile

No need of specific recycling operations

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins